

## Product information | TECHNICAL DATA SHEET

### MATTE FIXATIVE

400 ml, 9.7 Oz, 275 g.

#### GENERAL DESCRIPTION

Clearcoat, non-yellowing, fast drying, matte fixative. Ideal as a fixative and protective coat on objects used indoors.

#### FEATURES

- Very fast drying.
- Excellent matt finish.
- Not weather or water resistant.
- Easy application for protecting different artistic techniques.

#### APPLICATIONS

Recommended for use in the fine arts for protecting:

- Pastel
- Pencil
- Watercolor
- Charcoal drawings
- When a protective matte coat is required.

#### INSTRUCTIONS FOR USE

- Shake the aerosol well before using, approximately for one minute after hearing the sound of the mixer.
- Apply 1-3 coats of the product depending on the material that needs protection. Do a test prior to doing the final coat. Depending on the thickness of the layer applied, it may slightly whiten the surface's original color.
- For best results apply in thin layers. Three thin layers are always better than one thick one, and may be repainted within ten minutes with the same lacquer.
- Turn the aerosol upside down to clean out the valve after use. If the nozzle becomes blocked replace it with a new one.
- Never apply to equipment that is plugged in and use in well ventilated areas.
- Request safety datasheets.

#### PHYSICAL PROPERTIES

Color:	Transparent
Shine 60°:	<10 % matte
Dry to the touch (ASTM D-1640 ISO 1517):	10'
Completely dry (ASTM D-1640 ISO 1517):	20'
Thickness of dry layer (ASTM D-823 ISO 2808):	5-10 µ/capa
Theoretical yield (pintado en continuo):	2 m²
Thinner:	Alcohol Etilic / IPA
Product life:	(Well Stored) 5 Years
Recoating:	After 15' minutes
Condition for application:	T° min 8°C
	T° surface 5 a 40°C
	Humidity max. 85% R.H.P

#### IMAGE



#### LABEL



Laca Fijadora Mate / Matte Fixative  
EX014PRO998

#### CAP SYSTEM



**Soft Cap**  
Trazo medio ancho  
Medium wide line

#### PACKAGING

Nominal capacity: 400 ml.  
Heat resistance of packaging: <50°C  
Propellant: DME

**Box (6 units)**  
205 X 140 X 200 mm.

