

Product information | TECHNICAL DATA SHEET

RIM PAINT

400 ml.

GENERAL DESCRIPTION

Paint designed to restore car rims. Available in aluminum finish, it adheres perfectly to both aluminum rims and plastic hubcaps. Its fast-drying formula allows for quick handling and application.

FEATURES

- Very fast drying
- Good adhesion
- Long-lasting gloss and color
- Weather resistant

APPLICATIONS

- Automotive Industry
- Rims

INSTRUCTIONS FOR USE

- Shake the aerosol vigorously for about one minute after the mixing ball begins to rattle.
- Apply on clean, dry surfaces. On rusty metal, remove rust with a wire brush and apply an anti-rust primer if necessary.
- Apply in thin layers for best results. Three thin coats are better than one thick coat. Recoatable within 10 minutes using the same product.
- After use, turn the can upside down and press the nozzle until only gas comes out to clean the valve.
- If the nozzle becomes blocked, replace it with a new one.
- Do not apply on plugged-in equipment. Use in well-ventilated areas.
- Request safety data sheets if needed.

PHYSICAL PROPERTIES

Brinder type:	Thermoplastic acrylic
Color:	Aluminium
Dry to the touch (ASTM D-1640 ISO 1517):	10'
Total drying (ASTM D-1640 ISO 1517):	2h
Coat thickness (ASTM D-823 ISO 2808):	15 µ/capa (2 coats)
Theoretical yield (continuous painting):	2 m ²
Thinner:	Butyl acetate
Product life:	(Well Stored) 5 Years
Recoating:	After 10'
Painted resistance to heat:	150°C
Application conditions:	T: 5-35°C
	Humidity Max. 85% R.H.P.



APPEARANCE

DONUT

Indicates the paint color.

LID

Protects the valve and the nozzle.



65 mm.

LABEL

REF. N#



COD. BARRAS/BAR CODE

Aluminium Rim Paint / Aluminio Llantas
EX014PRO120W

CAP



Pocket Cap
Fino - Thin

PACKAGING

Nominal Capacity 400 ml
Container heat resistance: <50°C
Propellant: Aluminium: DME
VOC's: 617g/L

Box (6 units)
205 X 140 X 200 mm.

