

Product Information TECHNICAL DATA SHEET

VINYL AND FABRIC PAINT

400 ml.

GENERAL DESCRIPTION

Flexible paint formulated to restore the look and feel of leather and vinyl. It delivers strong adhesion on most plastics and creates a durable finish that stands up to wear and cracking.

FEATURES

- Very fast-drying.
- Good adhesion.
- For non-porous fabrics.
- High flexibility.
- Easy application and recoating.
- High coverage.
- Resistant to wear, peeling, and cracking.

APPLICATIONS

Ideal for restoring or customizing car seats, door panels, vinyl dashboards, armchairs, and sofas. Specifically designed to resist cracking, flaking, and chipping, ensuring long-lasting durability. Suitable for non-porous fabrics and rigid materials with some flexibility.

INSTRUCTIONS FOR USE

- Before use, shake the can vigorously for about 1 minute after the mixing ball begins to rattle.
- Apply to clean and dry surfaces. Remove any previous treatments from the surface such as conditioners, waxes, or paints.
For glossy surfaces, light sanding is recommended.
- For PP and PE, use an adhesion promoter beforehand.
- Apply 2-3 thin coats or until surface is evenly covered. Recoat after 15 minutes. Avoid handling until the product is fully dry. Perform a test on an inconspicuous area before full application.
- Do not apply to powered equipment, and use in well-ventilated areas.
- For further information, consult the safety data sheet.

PHYSICAL CHARACTERISTICS

Binder type:	Modified vinyl resin
Color:	Various
Gloss level (60°C):	"< 10% matte 15 - 50% satin > 70% gloss."
Touch-dry (ASTM D-1640 ISO 1517):	10-15 min
Fully dry (ASTM D-1640 ISO 1517):	6-12h
Dry coat thickness:	15 -20 µm
Theoretical coverage:	2.5 m ²
Product shelf life:	6 years
Recoat time:	20-30 min
Paint heat resistance:	90-95°C
Application conditions:	T: 5-35°C Max. humidity: 85% R.H.P. I

IMAGE



LABEL



CAP SYSTEM



Piel / Bulk Skin EX014PR0031M	Matt Black EX014PR0027M
Grís / Grey EX014PR0029M	Glossy Black EX014PR0027
Carbón / Charcoal Grey EX014PR0030M	Blanco / White EX014PR0028M

PACKAGING

Nominal capacity: 400 ml
Packaging heat resistance: <50°C
Propellant: DME

Box (6 units)
205 X 140 X 200 mm.

