

Product information | TECHNICAL DATA SHEET

TWO-COMPONENT COLOR

400 ml.

GENERAL DESCRIPTION

Two-component paint with great weather resistance and highly durable finishes. Designed for decorative, industrial and automotive purposes, for both indoor and outdoor.

FEATURES

- Easy to apply and repaint.
- Scratch-resistant.
- Multisurface adherence.
- Resistant to gasoline and chemicals.
- Highly-durable coating.

INSTRUCTIONS FOR USE

- Remove the white button from the lid. Turn the can upside down and place the button on the stem on the bottom side of the aerosol.
- Place the aerosol on a firm ground and press the white button with the palm of your hand.
- After activation, shake the aerosol for 2 minutes to ensure a good mixing of the product and catalyst.
- Remove the spray lock by first removing the spray nozzle. Place a screwdriver between the strap and lock ring. Lever the safety catch gently upwards and out.
- Apply on clean, sanded and dry surfaces.
- Apply in thin layers for best results. Recoat after 10-15 minutes.
- Pot life: 8 hours
- Recommended the use of 2K WEPRO Epoxy Primer for best results in corrosion resistance
- Turn the aerosol upside down to clean out the valve after use. If the nozzle becomes blocked replace it with a new one.
- Never apply to equipment that is plugged in and use in well ventilated areas. Do not breathe the aerosol vapors.
- Use personal protective equipment such as glasses, mask and gloves.
- Request safety datasheets.

PHYSICAL PROPERTIES

Binding type:	Hydroxylated acrylic
Hardener:	Isocyanate
Color:	Transparent
Gloss level:	Matt 15 (85°), Satin 40 (60°), Gloss >85 (20°)
Dry to the touch (ASTM D-1640 ISO 1517):	2 h
Total drying (ASTM D-1640 ISO 1517):	24 h
Coat thickness (ASTM D-823 ISO 2808):	20 microns/layer
Adherence (ASTM D-3359 ISO 2409):	B
Theoretical yield (continuous painting):	0,75m ²
*Potlife:	8 h
Shelf life:	(Well Stored) 3 Years
Application conditions:	T° environment min. 8°C T° surface min. 5-50°C Humidity Max. 85% R.H.P

* Depending on surrounding temperature.

070225



APPLICATIONS

Ideal for professional and DIY projects on a variety of surfaces: wood, metal, cast iron, galvanized steel, stainless steel, aluminium, glass, plaster, ceramic, concrete, masonry and many plastics (hard PVC, ABS, etc.). It can be applied without the need for a primer. On difficult surfaces, carry out a test application and/or apply a primer.

Specially designed for automotive, home improvement, industrial and professional use: indoor and outdoor furniture, vehicle parts, gutters, gates, railings, fences, garage doors, bicycles, metallic structures, aluminum profiles, industrial and agricultural machinery, urban furniture, etc

IMAGE



LABEL



CAP SYSTEM



Blanco / White EX014PK9010	Amarillo / Yellow EX014PK0Y14	Rojo / Red EX014PK3020
Negro Brillante / Glossy Black EX014PK9005	Negro Satinado / Satin Black EX014PK0937	Negro Mate / Matte Black EX014PK0964

PACKAGING

Nominal Capacity 400 ml.
Container heat resistance: <50°C
Propellant: DME

Box (6 units)
216 X 147 X 220 mm.



Certified ENTERPRISE according to quality and environmental standards ISO 9001 - ISO 14001

Made in Europe.