Product information | TECHNICAL DATA SHEET

WEPRO Water-Based Paint. Fluorescent colors. High-quality water-based formula with bio-based resin.
400 ml.

GENERAL DESCRIPTION

Fluorescent water-based multi-surface paint. The vibrant fluorescence and low-odor formula make it the ideal paint for decoration, restoration and signage projects. Designed with bio-based resins and a more environmentally friendly formula*.

*17% reduction in VOC content (lower VOC levels than solvent-based aerosols).

CHARACTERISTICS

- Easy-paint technology: smooth, drip-free valve.
- Fast-drying.
- Ultra-bright, vibrant fluorescent colors.
- Easy to apply.
- Can be used on many different materials.
- Recommended for indoor use. Low UV resistance.
- Can be varnished with an acrylic varnish.

INSTRUCTIONS FOR USE

- Shake the aerosol thoroughly before use, for about one minute after hearing the mixing ball.
- Apply to clean and dry surfaces. On rusted metal surfaces, first remove the corrosion using a wire brush. On plastics and polyester, first apply an anchoring coat.
- For a better, more eye-catching finish, apply a coat of matte white paint first.
- Apply in thin layers for the best results. Recoat after 30–45 minutes with the same paint. Depending on the thickness of the coat applied.
- Do not apply too much at once to prevent sagging.
- Turn the aerosol upside down to purge the valve after use. If the cap gets clogged,replace it with a new one.
- Do not apply to equipment or devices that are connected to an electricity supply, and use in well-ventilated areas.
- Request safety data sheets.

PHYSICAL CHARACTERISTICS

Binder type:	PU.
Color:	See chart
Shine	Matte < 10
Touch-dry (ASTM D-1640 ISO 1517):	45 min - 60 min*1
Fully dry (ASTM D-1640 ISO 1517):	72 hours
Coat thickness when dry (ASTM D-823 ISO 2808):	15 µm/layer
Recoat time:	after 45 min
Theoretical coverage (continuous painting):	Up to 3.5 m2 (depending on the color)
Product shelf life:	(with proper storage) 5 years
Application conditions:	Minimum ambient temperature: 8ºC
	Surface temperature: 5ºC – 35ºC
	Max. humidity 85% R.H.P

*1 *This will vary depending on the thickness of the coat.*

COLORS 4 colors

AMARILLO FLÚOR / *FLUORESCENT YELLOW*
EX014WF0600WM

ROJO FLÚOR / *FLUORESCENT RED*
EX014WF0602WM

FUCSIA FLÚOR / *FLUORESCENT FUCHSIA*
EX014WF0603WM

VERDE FLÚOR / *FLUORESCENT GREEN*
EX014WF0604WM

APPLICATIONS

Ideal for DIY and professional projects on a variety of surfaces: wood, metal, glass, timber, plaster, ceramic, stone, fabric, paper, papier-mâché, and styrofoam. Applying a white base coat is recommended to enhance the fluorescent effect.

It is ideal for signage, safety markings, decorative effects and creative projects.

APPEARANCE



CAP



Pocket Cap
Fino - Fine

PACKAGING

Nominal capacity: 400 ml.
Packaging heat resistance: <50ºC
Propellant: DME

Box (6 units)
205 X 140 X 200 mm.



Montana Colors, S.L. P.I. Clot del Tufau - 08295 Sant Vicenç de Castellet BARCELONA
T.: +34 938 332 787 - montana@montanacolors.com - www.montanacolors.com

COMPANY certified under quality and environmental standards.
ISO 9001 - ISO 14001
Made in Europe.